

Logic Programming

Prolog as Language

Temur Kutsia

Research Institute for Symbolic Computation
Johannes Kepler University of Linz, Austria
`kutsia@risc.uni-linz.ac.at`

Prolog as Language

- ▶ Syntax
- ▶ Operators
- ▶ Equality
- ▶ Arithmetic
- ▶ Satisfying Goals

Syntax

Terms:

- ▶ constant
- ▶ variable
- ▶ structure

Constants

- ▶ Naming (specific objects, specific relationships)
 - ▶ likes mary john book wine owns jewels
can_steal
 - ▶ a
 - ▶ void
 - ▶ =
 - ▶ 'george-smith'
 - ▶ -->
 - ▶ george_smith
 - ▶ ieh2304
- ▶ Integers (size is implementation dependent)

Non-Constants

The following symbols are not constants:

- ▶ `2340ieh` – Begins with number.
- ▶ `george-smith` – Contains dash.
- ▶ `Void` – Begins with capital.
- ▶ `_alpha` – Begins with underscore.

Variables

Begin with capital or with underscore:

- ▶ Answer
- ▶ Input
- ▶ `_3_blind_mice`

Anonymous variable: A single underscore

- ▶ `likes(john, _)`.
- ▶ Need not be assigned to the same variable `likes(_, _)`.

Structures

- ▶ Collection of Objects, *Components*, grouped together in one object.
- ▶ Help Organize.
- ▶ Make code more readable.

Structures

Example: Index Card for Library

- ▶ Author's Name
- ▶ Title
- ▶ Date
- ▶ Publisher
- ▶ Name could be split also first, last, etc.

Examples

▶ `owns (john, book) .`

▶ **One Level:**

`owns (john, wuthering_heights) .`

`owns (mary, moby_dick) .`

▶ **Deeper:**

`owns (john, book (wuthering_heights, bronte)) .`

`owns (john, book (wuthering_heights,
author (emily, bronte))) .`

Questions

- ▶ Does John own a book by the Bronte sisters?
`owns (john, book (X, author (Y, bronte))) .`
- ▶ For the yes/no question
`owns (john, book (_, author (_, bronte))) .`
(note that each `_` could be different)

Equality

An infix operator =

- ▶ $X = Y$

A match is attempted between expression X and expression Y

- ▶ PROLOG does what it can to match X and Y

Example: Instantiated

- ▶ X is uninstantiated.
- ▶ Y is an object.
- ▶ $X = Y$: X and Y will be matched.
- ▶ Thus X will be instantiated by the object Y .

```
?- rides(man,bicycle) = X.
```

```
X = rides(man,bicycle).
```

Example: Symbols

?- policeman = policeman.

Yes

?- paper = pencil.

No

?- 1066 = 1066.

Yes

?- 1206 = 1583.

No

Arguments Instantiated

- ▶ If the structures are equal then their arguments are matched.

```
?- rides(man,bicycle) = rides(man,X).
```

```
X = bicycle.
```

Arguments Instantiated

?- a(b, C, d(e, F, g(h, i, J))) =
a(B, c, d(E, f, g(H, i, j))).

B = b

C = c

E = e

F = f

H = h

J = j

Equality

```
?- X=X.
```

```
true
```

```
?- Y=X.
```

```
Y = X
```


Equality

?- X=Y, X=1200.

X = 1200, Y = 1200

?-

Arithmetic Comparisons

$X = Y$

$X \neq Y$

$X < Y$

$X > Y$

$X \leq Y$

$X \geq Y$

Arithmetic

```
?- 123 > 14.
```

Yes

```
?- 14 > 123.
```

No

```
?- 123 > X.
```

```
ERROR: Arguments are not sufficiently  
instantiated
```

```
?-
```

Example

- ▶ Prince was a prince during year, Year if Prince reigned between years Begin and End, and Year is between Begin and End.

```
prince(Prince, Year) :-  
    reigns(Prince, Begin, End),  
    Year >= Begin,  
    Year <= End.
```

```
reigns(rhodri, 844, 878).  
reigns(anarawd, 878, 916).  
reigns(hywel_dda, 916, 950).  
reigns(lago_ad_idwal, 950, 979).  
reigns(hywel_ab_ieuaf, 979, 985).  
reigns(cadwallon, 985, 986).  
reigns(maredudd, 986, 999).
```

Runs

- ▶ Was Cadwallon a prince in 986?
- ▶ Is Rhodri a prince in 1995?

```
?- prince(cadwallon, 986) .
```

Yes

```
?- prince(rhodri, 1995) .
```

No

```
?-
```

Who was a Prince When

- ▶ Who was the prince in 900?
- ▶ Who was the prince in 979?

```
?- prince(Prince, 900) .  
Prince = anarawd ;
```

No

```
?- prince(Prince, 979) .  
  
Prince = lagonadidwal ;  
  
Prince = hywelabieuaf ;
```

No

```
?-
```

Invalid Question

- ▶ When was Cadwallon a prince?

```
?- prince(cadwallon, Year).
```

```
ERROR: Arguments are not sufficiently  
instantiated
```

Calculating

- ▶ Calculating the Population Density of a Country:
Population over the Area

```
density(Country, Density) :-  
    pop(Country, Pop),  
    area(Country, Area),  
    Density is Pop/Area.
```

```
pop(usa, 305).  
pop(india, 1132).  
pop(china, 1321).  
pop(brazil, 187).
```

```
area(usa, 3).  
area(india, 1).  
area(china, 4).  
area(brazil, 3).
```


Questions

- ▶ What is the population density of USA?

```
?- density(usa, X) .
```

```
X = 101.667 ;
```

No

Questions

- ▶ What Country has which density?

```
?- density(X,Y).
```

```
X = usa
```

```
Y = 101.667 ;
```

```
X = india
```

```
Y = 1132 ;
```

```
X = china
```

```
Y = 330.25 ;
```

```
X = brazil
```

```
Y = 62.3333 ;
```

```
No
```

```
?-
```

Arithmetic Operations

$X + Y$

$X - Y$

$X * Y$

X / Y

$X \bmod Y$

How Prolog Answers Questions

Program:

```
female(mary) .
```

```
parent(C,M,F) :-mother(C,M) , father(C,F) .
```

```
mother(john,ann) .
```

```
mother(mary,ann) .
```

```
father(mary,fred) .
```

```
father(john,fred) .
```

Question:

```
?-female(mary) , parent(mary,M,F) , parent(john,M,F) .
```

How does it work?

Matching

- ▶ An uninstantiated variable will match any object. That object will be what the variable stands for.
- ▶ An integer or atom will only match itself.
- ▶ A structure will match another structure with the same functor and the same number of arguments and all corresponding arguments must match

How Is this Matched

?- sum(X+Y) = sum(2+3) .

X = 2,

Y = 3