

# Implementation of a Solution to the Conjugacy Problem in Thompson's Group $F$

James Belk, Nabil Hossain, Francesco Matucci, and Robert McGrail  
Bard College, Annandale-on-Hudson, NY, USA, 12504

Université Paris-Sud 11, Bâtiment 425, Bureau 21, F-91405 Orsay Cedex, France

belk@bard.edu, nh1682@bard.edu, francesco.matucci@math.u-psud.fr, mcgrail@bard.edu

## Abstract

We present an efficient implementation of the solution to the conjugacy problem in Thompson's group  $F$ . This algorithm checks for conjugacy by constructing and comparing directed graphs called strand diagrams. We provide a description of our solution algorithm, including the data structure that represents strand diagrams and supports simplifications.

## 1 Thompson's Group $F$ and Strand Diagrams

The elements of Thompson's Group  $F$  [3] are piecewise, linear homeomorphisms of the interval  $[0, 1]$  such that each piece has slope that is a power of 2 and, furthermore, the breakpoints between pieces take place at dyadic rational coordinates. The group operation is simply function composition. In a group, the **conjugacy problem** is the problem of determining whether any two elements are conjugate. The conjugacy problem is not solvable in general [5], but is solvable in certain cases.

A **strand diagram** [2] is a finite acyclic digraph embedded on the unit square. The digraph has a **source** along the top edge of the square and a **sink** along the bottom edge. Any internal vertex is either a **merge** or a **split** (Figure 1). Elements of Thompson's Group  $F$  can be translated to strand diagrams. Each element in a generating set corresponds to a particular strand diagram. A composition of such elements is represented by a concatenation of the associated strand diagrams.




Figure 1: A strand diagram, a merge, and a split (image taken from [2]).

## 2 Algorithm for the Conjugacy Problem in $F$

The algorithm to determine whether two strand diagrams inhabit the same conjugacy class proceeds as follows. First, we convert the strand diagrams to **annular strand diagrams**. This is achieved by a process called **closing**, in which sources are identified with sinks. Next, the annular strand diagrams are

reduced using a graphical rewriting system that is both confluent, terminating, and respects conjugacy [1]. Furthermore, any two connected and reduced annular strand diagrams  $s_1$  and  $s_2$  can be encoded into two planar graphs  $g_1$  and  $g_2$  respectively such that  $s_1$  and  $s_2$  represent conjugate elements if and only if  $g_1$  and  $g_2$  are isomorphic. Hence the problem reduces to checking whether two simplified planar graphs are isomorphic. Moreover, this enterprise can be carried out in linear time given a linear time planar-graph-isomorphism checker [4].




Figure 2: Algorithm Flowchart

## References

- [1] F. Baader and T. Nipkow. *Term Rewriting and All That*. Cambridge University Press, 1999.
- [2] J. Belk and F. Matucci. Conjugacy and dynamics in Thompson’s groups. Preprint, 2013.
- [3] J. W. Canon, W. J. Floyd, and W. R. Parry. Introductory notes on Richard Thompson’s groups. *Enseignement Mathématique*, 42: 215–256, 1996.
- [4] J. E. Hopcroft and J. K. Wong. Linear time algorithm for isomorphism of planar graphs (preliminary report). *Proceedings of the Sixth Annual ACM symposium on Theory of Computing*, 172–184, 1974.
- [5] P. S. Novikov. Unsolvability of the conjugacy problem in the theory of groups. *Izv. Akad. Nauk SSSR. Ser. Mat.*, 18: 485–524, 1954.